


**INVERTER 350W WITH  
AUTOMATIC SWITCH AND CHARGER  
(UPS)**



**SPECIFICATION**

ITEM	LSN - 350 C / 12V
OUTPUT POWER	CONTINUOUS POWER 350W
SURGE POWER	700W
STANDBY CURRENT	DC 12V < 0.7A
INPUT VOLTAGE	DC12V : 10V~15V
OUTPUT VOLTAGE	AC 230V
OUTPUT WAVEFORM	Pure Sine Wave 
EFFICIENCY	> 85%
INITIAL CHECKING	AUTO-DETECTING WRONG BATTERY CONT. ex. 12V / 24V
TOTAL HARMONIC DISTORTION	< 3%
OUTPUT REGULATION	< ± 5% INTELLIGENT PWM
OUTPUT FREQUENCY	50Hz CRYSTAL CONTROLLED.
FAN COOLING	CONTROL BY TEMPERATURE
OUTPUT SHORT	OUTPUT SHORT CIRCUIT PROTECTION
LOW BATTERY	< 10.5V ± 0.5V ALARM < 10V ± 0.5V SHUT DOWN & ALARM
OVER HEATING	> 65°C ± 5°C SHUT DOWN & ALARM
OVER LOAD	> 380W SHUT DOWN & ALARM
BATTERY POLARITY REVERSE	BY FUSE
FUSE	DC 12V : 20A * 2PCS
AC OUTLET	EUROPEAN TYPE : 1 AC OUTLET
※ BATTERY CHARGER	AUTO-INDICATING FULL BATTERY
※ CHARGER CIRCUIT	DC 12V : MAX. 10A
※ AUTOMATICAL SWITCH	AC LINE → INVERTER      INVERTER → AC LINE
※ TRANSFER TIME	AC LINE → INVERTER < 16ms      INVERTER → AC LINE < 20ms
DIMENSION (L*W*H)	385*135*79mm
NET WEIGHT	1.6Kg