



POWER SUPPLY SPECIFICATION
MODEL: MD25EU

INPUT

INPUT VOLTAGE	100 to 240 Vac
INPUT FREQUENCY	60 / 50 Hz
NO LOAD POWER CONSUMPTION	<0.1W
INPUT FULL LOAD CURRENT (at 100 Vac)	550 m A

OUTPUT

OUTPUT VOLTAGE (DC)	3.0 / 4.5 / 5.0 / 6.0 / 7.5 / 9.0 / 12.0V
OUTPUT CURRENT	2.25A

OVERALL PERFORMANCE

TOTAL OUTPUT POWER	27.0W Max
AVERAGE ACTIVE EFFICIENCY	Min 75.9% (for 3.0V); Min 78.8% (for 4.5V); Min 79.5% (for 5.0V); Min 83.5% (for 6.0V); Min 84.7% (for 7.5V); Min 85.5% (for 9.0V); Min 86.6% (for 12.0V)
EFFICIENCY AT LOW LOAD (10%)	Min 65.9% (for 3.0V); Min 68.8% (for 4.5V); Min 69.5% (for 5.0V); Min 73.5% (for 6.0V); Min 74.7% (for 7.5V); Min 75.5% (for 9.0V); Min 76.6% (for 12.0V)

PROTECTION

<input checked="" type="checkbox"/> OVER CURRENT PROTECTION	<input checked="" type="checkbox"/> SHORT CIRCUIT PROTECTION
<input checked="" type="checkbox"/> OVER VOLTAGE PROTECTION	<input checked="" type="checkbox"/> L.P.S (Limits for power source)
<input checked="" type="checkbox"/> OVER POWER PROTECTION	<input type="checkbox"/> AUTOMATIC THERMAL PROTECTION

HI-POT

INPUT TO OUTPUT	3000Vac 5 mA 50 Hz
INPUT TO CASE	3000Vac 5 mA 50Hz
OUTPUT TO CASE	500 Vac 5 mA 50Hz
ISOLATION RESISTANCE	100 M Ohms I/P-O/P I/P/Enclosure
APPLIANCE	Class II

ENVIRONMENTAL

OPERATING TEMPERATURE	0 °C to 25 °C
STORGE TEMPERATURE	-20 °C to 60 °C
OPERATING HUMIDITY	20%-85% RH. NON-CONDENSING
STORGE HUMIDITY	10%-90% RH. NON-CONDENSING

SAFFTY STANDARDS

SAFETY STANDARDS	EN 62368-1:2014+ A11:2017
EMC STANDARDS	EN 55032:2015 EN55035:2017

RELIABILITY

MTBF	30000 Hours min
------	-----------------

BURN-IN	4 Hours 25°C , full load, 220Vac, 50Hz
---------	--

MECHANICAL SPECIFICATION

DIMENSION	87.5 mm(L) x 51.0 mm(W) x 40.1mm(H) (excluded plug) 87.5 mm(L) x 51.0 mm(W) x 77.4mm(H) (included plug)
WEIGHT	200g MAX exclude packing
INPUT PLUG	Direct plug-in EU type
OUTPUT CORD	PVC, Length 1.8m
OUTPUT PLUG	Depends on client request

Appearance

