

PS200 HR-04

Solar submersible pump system for 4" wells

Applications

- Drinking water supply
- Pond management
- Irrigation
- Livestock watering
- Pressurizing systems

Characteristics

- Fast, failure-free installation
- Excellent serviceability
- High reliability and life expectancy
- Short Return of Investment (ROI) cycle
- Lower Total Cost of Ownership (TCO)

Technical data

Total dynamic head	max. 50 m
Flow rate	max. 0,73 m³/h
Vmp*	> 34 V
Voc	max. 100 V

Standards

CE 2006/42/EC, 2004/108/EC, 2006/95/EC

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market requirements.



Components

Controller: PS200

- Controlling and monitoring
- Control inputs for dry running protection, remote control etc.
- Protected against reverse polarity, overload and overtemperature
- Integrated MPPT (Maximum Power Point Tracker)
- Low voltage disconnect for battery operation

Motor: ECDRIVE 600-HR

- Maintenance-free brushless DC motor
- Water filled
- No electronics in the motor
- Submersion max. 250 m, IP68

Pump end: PE HR-04**

- High reliability and life expectancy
- Non-return valve
- Premium materials
- Optional: dry running protection




PS200 HR-04

Solar submersible pump system for 4" wells

Pump chart



Vmp* > 34 V



Dimensions and weights


Controller

H = 276 mm
H1 = 248 mm
H2 = 208 mm
W = 225 mm
W1 = 188 mm
D = 108 mm
D1 = 100 mm



Pump unit

A = 780 mm
B = 185 mm
C = 595 mm
D = 96 mm
S = 1,25 in



	Net weight
Controller	1,2 kg
Pump unit	11 kg
Motor	7,0 kg
Pump end	4,2 kg

*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

**Specify temperature range on order

BERNT LORENTZ GmbH & Co. KG

Kroegerskoppel 7, 24558 Henstedt-Ulzburg, Germany,
Tel +49 (0)4193 7548-0, Fax -29, www.lorentz.de

Sun. Water. Life.



Created by LORENTZ COMPASS 3.0

All specifications and information are given with good intent, errors are possible and products may be subject to change without notice. Pictures may differ from actual products depending on local market requirements and regulations.